

PANAFLEX BANNER – COATED PVC BACKLIT FLEX 800 G/M2 FIVE YEARS GUARANTEE

Product Features

- The surface of the Panaflex Banner has a self-cleaning function (when used outdoors, water stains and dust do not easily adhere to the surface of the substrate after rain)
- The unique film sticking process without glue residue.
- Premium acrylic surface treatment
- Anti-wicking treatment makes the base fabric not easy to leak.
- Effectively delay the color change and aging of the Panaflex Banner.
- UV resistance, five years warranty

Technical Data Sheet

Item Code	FBCB1010800TP5	Test Method
Base Fabric	1000D × 1000D 18 × 12	DIN EN ISO2060
Weight (GSM)	800	DIN EN ISO2286-2
Tensile Strength	Warp (N/5cm)	2895
	Weft (N/5cm)	1920
Tear Strength	Warp (N)	835
	Weft (N)	535
Adhesion Strength	Can not peel off	
Temperature	-30°C/+70°C	ISO13934-1:1999
Flame Retardant	B1	

Information contained in this document is based on our general experience and is given in good faith. However, we are unable to accept responsibility in respect to factors that are outside our knowledge or control.

Ink Printability

SOLVENT	ECO-SOLVENT	UV	LATEX	SCREEN PRINTING
		■		■



WhatsApp

Add: Room 912, No.3 Building, Shangdong Business Center, Haizhou District, Haining, Zhejiang, China
 Tel: +86-573-80776996 Fax: +86-573-80776998
 Mob/Skype/Wechat: +86-15858322153
 Email: jeff@hncmax.com cmflex@163.com



WeChat