



## PANAGRAPHICS SUBSTRATE – COATED PVC BACKLIT FLEX 680 G/M2 THREE YEARS GUARANTEE

## **Product Features**

- The surface of the Panagraphics Substrate has a self-cleaning function ( when used outdoors, water stains and dust do not easily adhere to the surface of the substrate after rain )
- The unique film sticking process without glue residue.
- Premium acrylic surface treatment
- Anti-wicking treatment makes the base fabric not easy to leak.
- Effectively delay the color change and aging of the Panagraphics Substrate.
- UV resistance, three years warranty

## **Technical Data Sheet**

Item Code		FBCB550680TP3	Test Method
Base Fabric		500D × 500D 18 × 18	DIN EN ISO2060
Weight (GSM)		680	DIN EN ISO2286-2
Tensile Strength	Warp (N/5cm)	1490	DIN53354
	Weft (N/5cm)	1140	DIN53354
Tear Strength	Warp (N)	340	DIN53363
	Weft (N)	240	DIN53363
Adhesion Strength		Can not peel off	
Temperature		-30°C/+70°C	ISO13934-1:1999
Flame Retardant		В	1

Information contained in this document is based on our general experience and is given in good faith. However, we are unable to accept responsibility in respect to factors that are outside our knowledge or control.

## **Ink Printability**

SOLVENT	ECO-SOLVENT	UV	LATEX	SCREEN PRINTING
				•

